



# ENTRY/EXIT STATION

Section Control Station

ZEAG Lane Section Control Station gives a high level of flexibility to allow control of vehicles in and out of controlled sectors within a parking facility (e.g. nested areas)



Parking  
technology

# HUB

## Base model

- Multilingual high contrast LCD display for user instructions (4x20 characters)
- Read/Write ticket unit for Magnetic stripe or Barcode tickets
- Illuminated navigation to guide customers step-by-step through the process
- Stainless steel housing
- Standard color - Housing (RAL 9006 White Aluminum) plus side/front panels (RAL 7021 Black Grey)
- Peripheral control unit
- Power Supply
- Heating and cooling units with separate thermostats
- Intercom call button and loudspeaker
- Individual security lock

## Options

- 10.4" color display and touchscreen
- Range of contactless RFID proximity readers
- Long range hands free automatic (AVI) readers
- Customized side/front panel color
- Customized housing and side/front panel colors
- Sea/Ocean special protective treatment
- Barcode scanner (1D or 2D options)
- Base (standard: 60mm, increased height for Chip & PIN: 200mm)
- Door open sensor options
- Proximity and AVI operation only (Lane Section Control Station only)

## Standard Features

- Online operation (RS422/485 or TCP/IP) or stand-alone operation
- Contract, Season or Monthly parking using a wide range of media (magnetic cards, barcode, proximity, AVI, LPR)
- PCI-DSS certified together with Parking Management System
- Gate control



### Peripheral Dimensions (W x D x H)

460 mm x 422 mm x 1360 mm  
18,1" x 16,6" x 53,3"

### Base Dimensions (H)

60mm; 200mm  
7,9"; 15,7"

### Power Consumption

114W (350W with heating)

### Electrical

90 - 240 VAC, 47-63 Hz

### Temperature

-20°C (-4F) to 50°C (122F)